



# DE-EE0008627 Preliminary Design Review January 17, 2020

## PROTECTED RIGHTS NOTICE

These protected data were produced by Columbia Power Technologies, Inc. Under agreement no. DE-EE0008627 with the U.S. Department of Energy and may not be published, disseminated, or disclosed to others outside the Government until five (5) years from the date the data were produced, unless express written authorization is obtained from the recipient. Upon expiration of the period of protection set forth in this Notice, the Government shall have unlimited rights in this data. This Notice shall be marked on any reproduction of this data, in whole or in part




---

# Agenda


- Project Overview and Objectives
- WETS Site Location
- Technoeconomic Metrics
- Schedule
- State of the Art
- Design Load Cases
- SeaRAY Preliminary Design
- SeaRAY Seafloor Garage Preliminary Design
- SeaRAY CONOPS
- DataRAY Preliminary Design

# Project Overview

- Goal is to design, deliver, and test a prototype low-power wave-energy-converter (WEC) that lowers the total cost of ownership and provides robust, new capabilities for customers in the maritime environment.
- This novel WEC system, the SeaRAY, is intended to be a mobile and deployable power, data and communications system for maritime sensors, equipment, and subsea vehicles



SeaRAY with mooring  
and seafloor garage



SeaRAY with various  
payloads

---

# Project Objectives

- Gather system requirements
- Evaluate design concepts
- Down-select most promising concept
  - meeting the identified market requirements
  - being technically feasible
  - promising cost competitiveness for the target market
- Design to meet requirements
- Test and validate

---

# Why Change to WETS as Primary Site Location?

- Better demonstrate SeaRAY capabilities
  - Transportability
  - Ease of deployment
  - Operational capabilities in a defense/security environment with US Navy support
  - Start in a lighter wave environment than PacWave
- Advance WEC-charged AUV system towards commercialization
- Potentially avoid being 1st to re-permit PacWave-North
- Gain deployment experience at WETS
- Utilize empty WETS berth

# Technoeconomic Metrics

Metric	Unit	Baseline	Targeted	% improvement from baseline	SeaRAY (DOE reference site*)	% improvement from baseline	SeaRAY (WETS)	% improvement from baseline
Levelized cost of energy (LCOE)	\$/watt-hour(Wh)	0.324	0.048	85%	0.024	93%	0.026	92%
Annual energy production (AEP)	kWh/year	629	2139	240%	10555	1577%	9671	1437%
Power to weight ratio (PWR)	W/kg	0.061	0.111	82%	0.189	210%	0.173	184%
Peak to average power ratio		40.7	24.0	41%	40.0	2%	43.7	7%



\*Depth for reference site 80m instead of 70m

# Schedule

<b>Task #</b>	<b>Task Description</b>	<b>Date</b>
M3.4/D3.4	Preliminary design	1/14
T4.0	Final design	1/14 - 4/21
D4.11	System Design and Integration Plan	4/21
M4.12	Final EDR and build drawings	4/21
T5.0	Component and subsystem V&V	1/24 – 6/16
D5.4	V&V report	6/16
T6.0	BP2 Permitting and Test preparations	1/31 – 4/24
D6.4	Permitting Status & permitting plan	4/24
D6.7	Preliminary IO&M Plan	3/27
T7.0	Go/No-Go	3/27-6/29
M7.1	Present Continuing Application	4/24
	BP2 start	6/29
T15	Deploy and Test WEC	9/9 – 3/17

# State of the Art

- Ocean Power Technologies




# Design Objectives

- Average energy generation above 1 kW
- Low-mass
- Rapidly deployable
  - System fits within 20' standard ocean container(s)
  - Minimal assembly work dockside
  - Able to use smaller, lightly manned vessels
- Mooring, data, and comms combined in one line
- Fully-integrated energy storage
- Capable of delivering continuous power as required
- Designed for PacWave North and WETS




# Design Load Cases




- 100-year return extreme sea condition
  - WETS:  $H_{m0} = 7.24\text{m}$ ,  $T_e = 12.98\text{s}$
  - PacWave North:  $H_{m0} = 17.31\text{m}$ ,  $T_e = 16.57\text{s}$

# Design Load Cases



# SeaRAY Description





- WEC
  - Nacelle – PTO housing
    - 1.3m OD x 5.18m (17') length
    - 3347 kg
  - Forward float – wave actuated
    - 0.85m OD x 5.33m (17'6") length
    - 1150 kg
  - Aft float – wave actuated, fixed to nacelle
    - 0.85m OD x 5.33m (17'6") length
    - 1150 kg
- Heave Plate
  - Large surface area to stabilize nacelle in water column
  - 3300 kg
- Garage
  - Gravity anchor
  - Batteries
  - Payload
  - 6800 kg

# SeaRAY Systems


System #	System Name	System Owner	EDR* Complete	Major Vendor
100	Hull	KO	Yes	Malin Marine
200	PTO	KO/LR	Yes	
300	Electric Plant	LR	Yes	AMS
400	SCADA	LR	Yes	AMS/APL
500	Auxiliary Sys.	AM/LR	Yes	APL
600	Outfit & Furnish	AM/KO	Yes	
700	Mooring/Umbilical	AM	Yes	EOM
750	Seafloor Garage	AM	Yes	EC-OG

\*Engineering Design Requirements

# 0100 Hull



# 0200 PTO



# 0200 PTO - Gearbox


## Gearbox

- PHQ1033
- Ratios: ... 91, 96, 120, ...
- Nominal Torque: 6,500 Nm
- Accel Torque: 10,000 Nm
- Peak Torque: 20,000 Nm



# 0200 PTO - Generator

- Permanent Magnet Traction Motor
- Used in high efficiency hybrid electric powertrains
- Three phase
- Low torque ripple
- SAE J455
- Heavy duty environmental standards



# 0200 PTO - Coupler

## Float Coupler

- PL100X145 AS-SS
- Stainless Steel
- Shaft OD: 3.9"
- Hub ID: 5.7"
- Torque: 8400 Nm




## Shaft Coupler

- EK6-9500
- Rated Torque: 10,000 Nm
- Max Torque: 20,000 Nm




# 0300 Electric Plant

- 3 Phase AC Generator
- AC to DC Conversion
- Operational Battery System in WEC
- Power Storage Battery on Seafloor
- Transmission WEC to Seafloor ~400V




# 0400 SCADA

- WEC's surface SCADA Network
- Electric Plant Condition, Monitoring & Control
- Battery Condition Monitoring
- Communication Systems
- WEC Auxillary System Monitoring and Control
- Position Monitoring
- Data Modems
- Mooring Monitoring



# 0400 SCADA

- Seafloor SCADA and Communications
  - Seafloor Battery Condition Monitoring
  - Mooring Monitoring System
  - Seafloor Sensor Payloads
  - Additional Package Support as defined
  - Data Modem



# 0500 Auxiliary Systems

- 0520 Emergency Systems
  - Fire Protection
  - Flooding Alarms
  - Access Alarm
  - Emergency-Stop (E-Stop)
  - Safety Controller
  - Safety Communications
- 0570 Bilge
  - DC Bilge pumps
  - Pumps controlled by 0520's flooding alarm sensor
  - Thermal Control provided by TEGs or heaters
- 0580 Surveillance
  - GPS Antenna System
  - IMU (inertial measurement device)
  - Onboard Camera system
  - AIS System



---

# 0600

- 0610 – Designation & Markings
- 0620 – Hull Fittings
- 0630 – Hull Penetrations
- 0640 – Paint (internal and external)
- 0645 – Anodes (passive corrosion mitigation)
- 0665 – Lightning Protection

# 0700 Mooring/Umbilical - EOM

- Combined mooring and umbilical cable
  - Top section: EOM's Chain
  - Bottom section: EOM's Stretch Hose
- Design loads at WETS: 39 T peak tension
  - Compared to 48 T peak at PacWave-North
- All hardware needs to fit in 20' shipping container




# 0750 Seafloor Garage

- Three main components:
  - Mooring gravity anchor
  - Battery bank
  - Sensor array payload
- Total wet weight < 5.64 Tn
  - Total dry weight > 6.5 Tn assuming steel anchor
  - Total dry weight > 9.3 Tn assuming concrete anchor
- Example: EC-OG's HALO




# CONOPS

Container #1




Container #2



# CONOPS

## Deployment Configuration




---

# DataRAY Design Considerations

- Auxiliary Power Unit
  - Target 10W Average Power Output
- Hosting WEC
- Self Contained
- Design Life - 2 Years

# DataRAY Overview



- Gyro
  - High Speed
    - 3000-5000 RPM
- PTO
  - Low Speed
  - Generator with Gearbox
- Vacuum Enclosure
  - 1e-3 to 1e-5 ATM

---

# DataRAY Bench Test

- NREL to perform bench test
- Objectives
  - Bearing test – effects of non torque loads
    - Break-in
    - Axial load
    - Radial load
    - Moment load
  - Gyro test
    - Windage measurement (torque)
    - Various vacuum levels